



נָדִיר
תַּעֲשִׂיּוֹת צִבֵּעַ

Akril Top

Acrylic paint with matt finish
for exterior and interior walls

Properties

- Especially high coverage rate
- Waterproof yet breathable
- Excellent adhesion
- High whiteness
- Easy to work with, odorless
- High UV resistance
- Constitutes an excellent base for metallic silicone wash (Pueblo).
- Non-toxic

Uses

Akril Top is suitable for painting a variety of exterior surfaces: Plaster, concrete, brick spray plaster, asbestos and drywall boards; may also be used on interior surfaces.

Product description

Excellent acrylic resin-based matt-colored paint, designed for exterior and interior walls. Especially high coverage rate.

Application instructions

- The application surface should be clean of any dust, dirt, oil or loose layers.
- Do not apply to wet walls.

Exterior walls:

- When applying on new surfaces (plaster, concrete, drywall, skim coat, etc.): After surface is completely dried (at least two weeks) apply Bonding Primer.
- When applying on old surfaces (old sprayed plaster, renovated or repaired walls, etc.): Peel any loose paint and perform touch-up. Then, apply Surface Strengthening Primer.

Interior walls:

- When applying on new surfaces (plaster, concrete, drywall, skim coat, etc.): After surface is completely dried (at least two weeks) apply Bonding Primer or First Coat.
- When applying on old surfaces (old sprayed plaster, renovated or repaired walls, etc.): Peel any loose paint and perform touch-up. After that, apply Interior Bond.

After surface preparation, thin Akril Top with 10-15% water and apply a first layer of Akril Top using a roller, brush or spray device. After the first coat has dried, a second coat may be applied and thinned as needed. Dry to touch time – three hours.

www.nadir.co.il • nadir@nadir.co.il





נדיר
תעשיות צבע

Safety warnings and instructions

- Do not apply **Akril Top** when rain is expected 36 hours after application.
- Do not apply to wet walls.
- Do not apply when the temperature is under five degrees or above 30.
- Do not mix this product with products not recommended by us.
- Non-ingestible. Keep out of reach of children.
- Keep your work area properly ventilated.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Technical data

Application temperature – 5-30 degrees Celcius



Color – white



Package – 18 liter and 5 liter



Composition – excellent acrylic resin, fillers and rheological materials



Cleaning – with water



Application – roller, brush, airless device, backpack sprayer



Storage – in a dry, shady place



Coverage rate – for 18 liters about 60 sqm in two coats (depending on surface absorption).



Fully dried – in 24 hours.



Shelf life – 12 months in original packing



Density – 1.5 kg/liter



Since 1990, **Nadir Color Industries** has been at the forefront of the paint and decorative coating industry. Nadir has attained a position of prominence among the foremost manufacturers in Israel and worldwide through its ability to respond to changing market needs, while at the same time remaining creative and innovative, and fulfilling its commitments to its customers.