



limestone Tuscany

Mineral plaster with a natural gravel appearance

Product description:

limestone Tuscany mineral plaster with a natural gravel look.

Uses:

limestone Tuscany may be used as a top coating and finishing layer, or as a single layer plaster for exterior and interior use.

Properties:

- Suitable as a top coating, a finishing coating or a single layer plaster.
- Designed for both exterior and interior use.
- Natural gravel look.
- Non-toxic and breathable.
- Excellent adhesion.

Surface preparation:

• **limestone Tuscany** as a finishing layer: All plaster works including repairs, tying of scaffolding in window areas and disconnecting of scaffolds from the wall, to enable continuous, uninterrupted work. Wash all dust from the wall. limestone Tuscany is applied to damp walls.

• **limestone Tuscany** as single-layer plaster: Spread a cement scratch coat and compact with a spatula. Install metal corners, mount window sills and, if needed, steel rulers to set the layer's thickness. Allow 14 days for the scratch layer to dry, before applying **limestone Tuscany**.

Application instructions:

- Add **limestone Tuscany** to clean water while mixing with a manual electric mixer or a cement mixer, until suitable thickness is obtained. Wait 2-3 minutes and mix again. Recommended amount of water for 25 kg **limestone Tuscany**: 4.5 liters. After mixing with water, **limestone Tuscany** may be used for up to three hours.
- limestone Tuscany is applied with a spatula (trowel). Level the limestone Tuscany layer with a plastering darby, and compact with a trowel. Wait 2-3 hours, then comb the **limestone Tuscany** with a round saw blade or nail board until getting the desired texture.
- The day after applying, scrape off excess plaster with a trowel or an upside down saw. The day after applying, it is important to wet the **limestone Tuscany** with clean water (by spraying a mist) from bottom up, uniformly, over the entire wall surface.
- To prevent collection of dirt and dust, and to improve Tuscany's sealing capability, apply NSG-303 sealer, 0.3 liter/m², at least 3-4 days after finishing.

www.nadir.co.il



limestone Tuscany

Technical data

Application temperature – 5-30 degrees Celcius



Color – natural gravel



Package: 25 kg sack



Composition – gravel aggregate, white cement, lime, silica, minerals, water-repellent substances.



Cleaned with water



Application – with a plaster saw or a trowel



Storage – in a dry, shady place



Coverage rate – about 15-20 kg/sqm



Drying time: 2-3 hours.
Fully dried: 72 hours



Density - 1.79 kg/liter



Shelf life: 12 months in original packing, in a shady, dry area.



Safety warnings and instructions:

- Do not apply **limestone Tuscany** when rain is expected 36 hours after application.
- Do not apply when the temperature is under five degrees or over 30.
- Do not mix this product with products not recommended by us.
- Not for internal consumption; keep out of reach of children.
- Keep storage area properly ventilated.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

www.nadir.co.il

אזור תעשייה פרדס חנה, ת.ד. 1285, 37000 • טל. 04-6271003 • פקס. 04-6273668