



Lorenzo

Unique paint in matt finish, for painting walls and ceilings.

Product description:

Paint in matt finish used for painting all types of colored, acrylic and mineral plaster, and painting walls and ceilings.

Uses:

A unique paint used for renewing all types of colored plaster, as well as painting plasterboard walls, ceilings, and more. Lorenzo provides the perfect coating for exterior and interior use.

Properties:

- Water-based paint with matt finish for perfect coverage.
- High adhesion for a wide variety of surfaces.
- Waterproof, yet with respiration capability.
- Ready for use, designed for both exterior and interior use.
- Easy to work with.
- Non-toxic and odorless.
- High UV resistance.

Application instructions:

- The application surface should be clean of any dust, dirt, oil or loose layers.
- Do not apply to wet walls.

Exterior walls:

- When applying on new surfaces (plaster, concrete, drywall, skim coat, etc.): After surface is completely dried (at least two weeks) apply Bonding Primer.
- When applying on old surfaces (old sprayed plaster, renovated or repaired walls, etc.): Peel any loose paint and perform touch-up. Then, apply Surface Strengthening Primer.

Interior walls:

- When applying on new surfaces (plaster, concrete, drywall, skim coat, etc.): After surface is completely dried (at least two weeks) apply Bonding Primer or First Coat.
- When applying on old surfaces (old sprayed plaster, renovated or repaired walls, etc.): Peel any loose paint and perform touch-up. Then, apply Interior Bond (Bonder All Interior).
- After preparing the surface, using a roller or a brush, apply a coat of **Lorenzo**.
- The first coat of **Lorenzo** may be thinned with 10-15% water.
- After applying the first coat, a second coat may be applied, thinned as needed.
- Drying time between coats: At least three hours.

www.hadasi.co.il



Lorenzo

Technical data

Application temperature – 5-30 degrees Celcius



Color – Nadir catalog colors



Package – 18 liter and 5 liter steel drums



Composition – special resins, rheological materials, fungus and mold-repellent substances, and selected pigments.



Cleaned with water



Storage: dry, shady place



Application – brush, roller



Drying time between coats: 3-4 hours. Fully dried: 48 hours.



Coverage for 18 liters: about 60 sqm



Shelf life: 12 months in original packing



Density – 1.5-1.6 kg/liter



Safety warnings and instructions:

- Do not apply **Lorenzo** when rain is expected 36 hours after application.
- Do not apply to wet walls.
- Do not apply when the temperature is under five degrees or over 30.
- Do not mix this product with products not recommended by us.
- Not for internal consumption; keep out of reach of children.
- Keep storage area properly ventilated.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

www.nadir.co.il

אזור תעשייה פרדס חנה, ת.ד. 1285, 37000 • טל. 04-6271003 • פקס. 04-6273668