



## Sand Textured Paint

Unique paint in matt finish, for renewal of colored plaster.

### Product description:

Paint with a fine sand appearance in matt finish, designed for renewal of all types of colored plaster, acrylic and mineral, waterproof yet breathable. High UV resistance.

### Uses:

- Used for renewal of spray plaster, and colored and mineral plaster.

### Properties:

- Maintains the authenticity of the look and texture of colored plaster.
- Water-based paint with a matt finish that provides excellent coverage.
- High adhesion on various types of surfaces.
- Waterproof, yet with respiration capability.
- Ready for use, designed for both exterior and interior use.
- Easy to work with.
- Non-toxic and odorless.
- High UV resistance.

### Application instructions:

- The application surface should be clean of any dust, dirt, oil or loose layers.
- Do not apply to wet walls.

#### Exterior walls:

- When applying on new surfaces (plaster, concrete, drywall, skim coat, etc.): After the strata is completely cured (at least two weeks) apply "bonding primer".
- When applying on old surfaces (old sprayed plaster, renovated or repaired walls, etc.): Peel any loose paint and perform touch-up. Then, apply Surface Strengthening Primer.

#### Interior walls:

- When applying on new surfaces (plaster, concrete, drywall, skim coat, etc.): After surface is completely dried (at least two weeks) apply Bonding Primer or First Coat.
- When applying on old surfaces (old sprayed plaster, renovated or repaired walls, etc.): Peel any loose paint and perform touch-up. Then, apply Interior Bond (Bonder All Interior).
- After preparing the surface, using a roller or a brush, apply a coat of **Sand Textured Paint**.
- The first coat of **Sand Textured Paint** may be thinned with 10-15% water.
- After applying the first coat, a second coat may be applied, thinned as needed.
- Drying time between coats: At least three hours.

[www.nadir.co.il](http://www.nadir.co.il)

אזור תעשייה פרדס חנה, ת.ד. 1285, 37000 • טל. 04-6271003 • פקס. 04-6273668



## Sand Textured Paint

### Technical data

Application temperature: 5-30 degrees celcius

Package – 18 liter and 5 liter steel drums

Cleaned with water

Storage: dry, shady place

Drying time between coats: 3-4 hours. Fully dried: 48 hours.

Shelf life: 12 months in original packing



Color – Nadir catalog colors

Composition – special resins, selected aggregates, rheological materials, fungus and mold-repellent substances, and selected pigments.

Application – brush or fur roller

Coverage for 18 liters: about 60 sqm

Density – 1.5-1.6 kg/liter



### Safety warnings and instructions:

- Do not apply **Sand Textured Paint** when rain is expected 36 hours after application.
- Do not apply to wet walls.
- Do not apply when the temperature is under five degrees or over 30.
- Do not mix this product with products not recommended by us.
- Not for internal consumption; keep out of reach of children.
- Keep storage area properly ventilated.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

[www.nadir.co.il](http://www.nadir.co.il)

אזור תעשייה פרדס חנה, ת.ד. 1285, 37000 • טל. 04-6271003 • פקס. 04-6273668