



Veneciano

Decorative mineral coating

Product description:

Veneciano is an especially smooth mineral coating, with an elegant glazed look and a natural gloss.

Uses:

Veneciano is used as a decorative especially smooth mineral coating with a glazed appearance and a natural shine, applied in two coats. Veneciano has an especially high rate of coverage; its application is easy, convenient and quick.

Properties:

- Pit lime-based; breathable.
- Easy smoothing and polishing.
- Applied in two coats.
- Various degrees gloss.
- Excellent adhesion.
- Ready for use, designed for interior use.
- Non-toxic and easy to use.

Application instructions:

- The application surface should be clean of any dust, dirt, oil or loose layers.
- Do not apply to wet walls.
- Smooth out the application surface before spreading Veneciano.

Exterior walls:

• When applying on a new surface (concrete, plaster, etc.): After the substrate is completely cured (at least two weeks) apply Bonding Primer. When applying on old surfaces (old sprayed plaster, renovated or repaired walls, etc.): Peel any loose paint and perform touch-up. Then, apply Surface Strengthening Primer.

Interior walls:

• When applying on a new surface (concrete, plaster, etc.): After surface is completely dried (at least two weeks) apply Bonding Primer or First Coat. When applying on old surfaces (old sprayed plaster, renovated or repaired walls, etc.): Peel any loose paint and perform touch-up. After that, apply Interior Bond.

• First coat: Apply the Veneciano with a spatula in circular movements, until the wall is fully covered and smooth. Walls may be sanded with fine sandpaper until obtaining a smooth surface, as needed.

• For the first coat, make sure the wall is fully covered and absolutely dry (takes 2-3 hours).

• Finishing coat: Using a stainless steel spatula or trowel, in circular movements, apply a very thin coat of Veneciano. Wipe immediately according to desired texture.

• Smoothing and polishing: After 1-2 minutes, in circular movements, compact the Veneciano using a trowel and/or clean stainless steel spatula until achieving the desired smoothness and shine. For a smooth finish and glazed shine, continue polishing with edge of the trowel.

• To achieve a higher gloss and improve impermeability, apply Beez Wax after the Veneciano is absolutely dry (about 12 hours).

www.nadir.co.il

Veneciano

Technical data

Application temperature: 5-30 degrees Celcius



Color – Nadir catalog colors



Package – 25 kg, 7 kg



Composition – year-old pit lime, powdered marble dust, anti-bacteriological materials, resin and rheological substances.



Cleaned with water



Application – with stainless steel spatula



Storage – dry, shady place



Coverage rate – about 0.5 kg/m² depending on type of surface and desired texture



Contact dryness: one hour; second coating: 2-3 hours; fully dried: 12 hours



Density – 1.50 kg/liter



Shelf life: 12 months in original packing



Safety warnings and instructions:

- Do not apply **Veneciano** when rain is expected 36 hours after application.
- Do not apply to wet walls.
- Do not apply when the temperature is under five degrees or over 30.
- Do not mix this product with products not recommended by us.
- Not for internal consumption; keep out of reach of children.
- Keep storage area properly ventilated.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

www.nadir.co.il